

# 3M™ Green Corps™ Cut-Off Wheels

- *Fast*
- *Durable*
- *Clean*



**3M** Innovation



# 3M™ Green Corps™ Cut-Off Wheel

Now Available In 12",14" & 16"

The 3M Green Corps Cut-Off Wheels contain 3M patented Cubitron™ abrasive grain and they last significantly longer than conventional aluminum oxide cut-off wheels.

These large diameter Green Corps Cut Off Wheels are ideal for general-purpose metal cutting applications and are designed to provide high cut rates and long life on most materials - especially stainless steel.

The Green Corps Cut Off Wheels can also be used to cut mild steel, aluminum, copper and fiberglass.



## Advantages

- Last significantly longer than conventional abrasives cut-off wheels
- Cuts much faster than conventional abrasives cut-off wheels
- Less noise and dust generation
- Gives a clean and accurate cut each time, hence eliminating need for secondary working
- Heat resistant and will not discolor work piece

## Product Availability & MOS

Stock No	Size	Maximum Operating Speed (MOS)	
		m/s	rpm
XC002056999	12" (305x3x25.4mm)	80 m/s	5,100 rpm
XC002057005	14" (355x3x25.4mm)	80 m/s	4,400 rpm
XC002057013	16" (405x3.5x25.4mm)	71 m/s	3,400 rpm

Packaging: 5 Packs/Box (5 Wheels/Pack)

## Safety First

Always use properly guarded tools, follow maximum operating speed recommendations and wear proper face and body protection.



**Product Use:** All statements, technical information and recommendations contained in this document are based upon tests or experience that 3M believes are reliable. However, many factors beyond 3M's control can affect the use and performance of a 3M product in a particular application, including the conditions under which the product is used and the time and environmental conditions in which the product is expected to perform. Since these factors are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

**Warranty and Limited Remedy:** Unless stated otherwise in 3M's product literature, packaging inserts or product packaging for individual products, 3M warrants that each 3M product meets the applicable specifications at the time 3M ships the product. Individual products may have additional or different warranties as stated on product literature, package inserts or product packages. **3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OR DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. If the 3M product is defective within the warranty period, your exclusive remedy and 3M's and seller's sole obligation will be, at 3M's option, to replace the product or refund the purchase price.

**Limitation of Liability:** Except where prohibited by law, 3M and seller will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

**Safety Information:** Always use appropriate protective glasses, face shields and body protection. Do not exceed maximum operating speeds. Use guards provided with machine. Follow safety operation procedures posted in work areas.

