## **Scotch<sup>®</sup> Paper Masking Tape** 202

Product Description	Scotch <sup>®</sup> Paper Masking Tape 202 is a high performance, excellent paint masking tape for holding, protecting and bundling where a pressure sensitive tape is needed.			
Product Construction	Backing	Adhesive	Color	Standard Roll Length
	Smooth crepe paper treated with a solvent resistant satu		Tan	55 m (60.17 yds.)*
	*Available in metric widths (eg, 24 mm corresponds to 1 inch).			
Typical Physical Properties	Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.			
	Adhesion to Steel:	27 oz /ip width (11 N	1/100 mm)	ASTM Test Method
	Tensile Strength:	37 oz./in. width (41 N/100 mm) 27 lbs./in. width (472 N/100 mm)		D-3330 D-3759
	Elongation at Break:	8%		D-3759
	Tape Thickness:	6.3 mils (0.16 mm)		D-3652
	Temperature Use Range:	Up to 250°F (121°C)	for 30 minutes	
Features	• Has been laboratory test temperatures of up to 24 time performance may b can vary dependent on s bakes), type of paint inv We recommend testing your needs.	50°F (121°C) for 30 to be higher or lower for surface type, procession rolved as well as the to	minutes. The r a given appl ing conditions temperature o	actual temperature and ication. Clean removal s (such as multiple f the surface at removal
	• Excellent transfer resistance to "difficult to remove from" surfaces like EDPM rubber moldings.			
	• Tests indicate it is better than conventional masking tapes for sunlight resistance, it is still advised that it not be subjected to outdoor exposure or prolonged periods of sunlight as tape may become difficult to remove.			
	<ul><li>of sunlight as tape may become difficult to remove.</li><li>Can be qualified for PPP-T-42C, Type I, (CID-A-A-883A).</li></ul>			



## Scotch<sup>®</sup> Paper Masking Tape

202

Store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton. To obtain best performance, use this product within one year from date of manufacture.		
Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.		
Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.		
Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.		
This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9001:2008 standards		



Industrial Adhesives and Tapes Division 3M Center, Building 225-3S-06 St. Paul, MN 55144-1000 800-362-3550 • 877-369-2923 (Fax) www.3M.com/industrial



Scotch is a registered trademark of 3M. Printed in U.S.A. ©3M 2011 70070944296 (2/11)